



University of Nebraska at Omaha

WAYFINDING

WAYFINDING AND SIGNAGE STANDARDS DOCUMENT



FINAL

August, 2012

Developed by Corbin Design, Inc.

109 East Front, Suite 304

Traverse City, MI 49684

www.corbindesign.com

TABLE OF CONTENTS

Introduction	3
Objective One: Sustain	4
Objective Two: Clarify	5
Objective Three: Direct	6
Exterior Signage	7-39
Exterior Sign Type Array	7
Fabrication Specifications	8-10
Materials, Finishes, Logos and Symbols	11
Cx-1a	Dodge Campus Identifier - Retrofit with LED Display
	12
	UNO Prototype Icon Logo Details
	13
Cx-1b	Pacific Campus Identifier - Retrofit with LED Display
	14
Cx-1c	Pacific Campus Identifier NEW SIGN BASE AND FOUNDATION
	15
Cx-2a	Campus Identifier - Retrofit
	16
Cx-2b	Center Campus Identifier NEW BASE AND FOUNDATION
	17
Dx-1	Pedestrian Map Kiosk (Large)
	18
Dx-2	Vertical Pedestrian Building Identifier with Map
	19
Gx-1	Trailblazer
	20
Gx-2	Vehicular Guide (6" text)
	21
Gx-3	Vehicular Guide (4" text)
	22
Gx-4	Vehicular Guide with Digital Message Board (4" text)
	23
Gx-5	Vehicular Guide (4" text)
	24
Gx-6	Pedestrian Guide
	25
Ix-1b	Building Identifier - Retrofit
	26
Ix-2	Vertical Vehicular Building Identifier
	27
Ix-3	Vertical Pedestrian Building Identifier
	28
Ix-4a	Building Identifier, Small Horizontal
	29
Ix-4b	Building Identifier, Large Horizontal
	30
Ix-5	Parking Identifier
	31
Ix-6	Parking Identifier with Digital Message Board
	32
Ix-7 and Ix-7a	Parking Identifier, Wall Mounted
	33
Ix-8	Street Identifier
	34
Ix-9	Building Identifier, Wall Mounted
	35
Rx-1 and Rx-1a	Regulatory
	36
Rx-2 and Rx-2a	Regulatory, Wall Mounted
	37
Tx-1	Temporary
	38
Vx-1 and Vx-1a	Vinyl on Glass
	39

Interior Signage	40-66
Interior Design Array	40-42
Fabrication Specifications	43-45
Graphic Standards	46
Mounting Guidelines	47
D-1	Building Directory
	48
D-1a	Monitor Display Frame
	49
	Monitor Content Layout
	50
D-1b	Freestanding Monitor Display
	51
D-2	Faculty Directory
	52
G-1	Wall Guide, Large
	53
G-2	Wall Guide, Small
	54
G-3	Wall Guide, Acrylic
	55
I-1	Primary Department Identifier
	56
I-1a	Room Monitor Display Frame
	57
I-2 and I-2a	Room Identifier, Large
	58
I-3 and I-3a	Room Identifier, Small
	59
I-4, I-4a, I-4b and I-4c	Room Number Identifier
	60
I-5 and I-5a	Office Identifier
	61
I-6 and I-6a	Office Identifier, Small
	62
N-1, N-1a, N-1b and N-1c	Notice Insert
	63
O-1 and O-2	Overhead Signs
	64
R-1	Regulatory
	65
T-1	Freestanding Temporary Insert
	66

INTRODUCTION

This document is the result of the development of a comprehensive interior and exterior wayfinding system for UNO. It contains the foundational logic and assumptions of the wayfinding program, a complete review of all standards for wayfinding signage on campus, and recommendations & contact information for ongoing maintenance as the campus grows and changes.

Our preliminary analysis and subsequent logic, language and design has been arranged around these three primary objectives:

SUSTAIN

Build internal protocols to simplify information sharing among departments; create one go-to group for wayfinding changes and ongoing program review.

CLARIFY

Establish common terminology, consistent with UNO culture; build intuitive wayfinding logic based on key decision points, and create standards for system implementation and expansion.

DIRECT

Create the visual elements designed to display wayfinding information.

SCOPE OVERVIEW

Through the Core Team of representatives that served as our primary client interface, we’ve addressed the following project objectives:

- Provide a more inviting, self-directed, non-intimidating atmosphere for new visitors, students and their parents.
- Develop a visual design concept that reflects the University’s identity standards, is timeless in its aesthetic and respects the character, history and ambiance of each UNO campus.
- Create a wayfinding signage vocabulary that meets the immediate and long-term needs of the University.
- Determine a plan for phased implementation.
- Work with and seek advantages of Nebraska Department of Road’s (NDOR) guidelines as addressed in the State’s Manual for Uniform Traffic Control Devices (MUTCD).

UNO Wayfinding Team:


Sara Woods	Associate Dean, CPACS
Robert Carlson	Chair, Art & History, Faculty Senate
John Amend	Director, Facilities Mgt. & Planning
George Killian	Campus Architect, Facilities
Diane Sunde	Project Coordinator, Facilities
Stan Schleifer	Director, Support Services
Mollie Anderson	Director, Human Resources
Ethan Anderson	Operations Coordinator, Athletics
Steve Lendt	Director, Information Services
Tim Kaldahl	Director, University Relations
Donna Hathaway	Assistant to the Chancellor
Rita Henry	Assistant Vice Chancellor
William Pickett	Director, University Housing
Annie Bougger (Rotating)	Asst. Dir. of Events, NU Foundation
Scott Durbin	Vice President, Student Gov’t.
	Alumni Association Board Member

Corbin Design Team:

Mary Lou Piehl	Project Manager
Jeff Frank	Senior Designer
Mark VanderKlipp	President, Principal In Charge

JOURNEY MAP

This graphic describes a typical visitor journey and diagrams the second and third objectives in summary form.



A wayfinding program, properly implemented, brings about both physical and cultural changes. The solutions we’ve proposed throughout this process have established language, standards and protocols that must be managed appropriately by the internal wayfinding team.

Since Corbin Design’s scope of work is now complete, the UNO team’s responsibilities have begun in earnest; far from being simply a signage project, we view wayfinding as a “communications fitness program,” maintained on a biannual basis, by individuals throughout UNO. With each member of the Wayfinding Team doing their part, the wayfinding system will be a success.

The timing of this initiative is excellent. With the introduction of the new UNO identity elements, an upgrade to campus signage and communications will be expected; this initiative has been viewed as an opportunity to introduce and enhance the new UNO brand, while at the same time creating standards for consistent application and, above all, building a better student, alumni and campus visitor experience.


We’re grateful for the opportunity to have been your wayfinding consultants, and look forward to hearing from you of the successes of this initiative.

OBJECTIVE ONE:

SUSTAIN



Build internal protocols to simplify information sharing among departments, create one go-to group for wayfinding changes and consistent ongoing program review.



This org chart demonstrates areas of responsibility for each Wayfinding Team member:

- The Campus Visitor experience should be reviewed and assessed on a biannual basis. Requests for changes to wayfinding information will be directed to a single member of the Wayfinding Team. Those requests will be reviewed at the biannual meeting.
- Facilities and University Relations comprise the heart of the wayfinding team. IS, HR and other groups would be involved as issues arise that require their specific expertise.
- Since each of these groups have a particular responsibility to communicate at each point of the Journey Map, they will view suggested changes/ additions to the wayfinding program through the filter of established UNO standards and protocols.
- Participants in the Wayfinding Team are charged with upholding the standards in this book, and educating others about the need for effective, consistent wayfinding. The Charter Documents provided to each team member outline specific responsibilities.
- As a group, they will collaborate to affect the communications for which they have responsibility. Illustrative examples are shown here, though this grid is by no means complete.

OBJECTIVE TWO:

CLARIFY



Establish common terminology, consistent with UNO culture; build intuitive wayfinding logic based on key decision points, and create standards for system expansion.

TERMINOLOGY

Primary changes to UNO Terms:


Previous Terms	New Terms
One Campus	One University
Three Locations	Three Campuses
Dodge Location	Dodge Campus
Pacific Location	Pacific Campus
Center Location	Center Campus
Parking Garage	East Parking Garage
Student Parking Garage	West Parking Garage

Approved exterior wayfinding language:

DESTINATION NAME	CAMPUS
Allwine Hall	Dodge
Arts & Sciences Hall	Dodge
International Studies and Programs	
Child Care Center	Dodge
CPACS	Dodge
College of Public Affairs & Community Service	
Criss Library	Dodge
Dome, The	Center
Durham Science Center	Dodge
Kountze Planetarium	
Eppley Administration Building	Dodge
HPER	Dodge
Health, Physical Education & Recreation	
Health Services	
Kayser Hall	Dodge
Mammel Hall	Pacific
Maverick Village	Dodge
Milo Bail Student Center	Dodge
Peter Kiewit Institute, The	Pacific
Roskens Hall	Dodge
Sapp Fieldhouse	Dodge
Scott Conference Center and Residence Hall	Pacific
Scott Court	Pacific
Scott Village	Pacific
Strauss Performing Arts Center	Dodge
University Village	Dodge
W.H. Thompson Alumni Center	Dodge
Weber Fine Arts Building	Dodge
UNO Art Gallery	
UNO Theatre	
Welcome Center	Dodge
Pre-Admissions and Orientation	

LOGIC

Primary circulation logic:



OBJECTIVE THREE:

DIRECT



Create the visual elements designed to display wayfinding information.

PRINT, WEB AND MOBILE MEDIA

University Relations, as members of the Wayfinding Team, should engage in regular reviews of their print, online and social media tools. By doing so, they will be receiving feedback and confirmation from their peers, and setting an example for proper use of wayfinding logic.

The current rebranding effort has been a perfect catalyst for creating these new internal protocols, tying standards for wayfinding into the broader brand strategy.

Wayfinding content should be incorporated into:



- Campus pre-visit materials
- Information to alumnae, families and prospective students
- Internal faculty and staff training communications
- External communication vehicles to community members, sports/science camp attendees, etc.
- Media/PR and Social Media outlets

Similarly the UNO IS department, as a member of the Wayfinding Team, should engage in regular reviews of their electronic communications. From interactive signage across campus, to information provided to the Welcome Center, Alumni Center and switchboard, to public and internal Websites, this information must be consistently applied.

Individual buildings may create their own interior wayfinding direction as needed. Mammel Hall has already done this, and we assume Four Winds will continue to develop these internal floor plan maps. It is important that these floor maps have similar graphic features, consistent with other mapping standards throughout the UNO campus. We recommend use of a plan view map, as shown in the pedestrian kiosk graphic to the right.




These are the tools that will be used to display and communicate UNO wayfinding information:

Print, Mobile & Web-based Tools



NOTE: each of the current versions of these tools contain outdated logic, language and graphics. They will need to be updated as this program begins.

This campus map will appear on Pedestrian signage throughout the UNO campuses. Visitors with smartphones will be able to access more information via the QR code at the bottom.



Sign Type Array

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision

Client

University of
Nebraska at Omaha

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236

FABRICATION SPECIFICATIONS: EXTERIOR SIGNAGE

A. Quality Standards

The materials, products, equipment and performance specifications described within establish a standard of required function, dimension, appearance, performance and quality to be met by the Fabricator.

B. Structural Design

Details on design intent drawings indicate a design approach for sign structure but do not necessarily include all fabrication details required for the complete structural integrity of the signs, including consideration for static, dynamic and erection loads during handling, erecting, and service at the installed locations, nor do they necessarily consider the preferred shop practices of the individual Fabricators. Therefore, it shall be the responsibility of the Fabricator to perform the complete structural design and engineering of the signs and to incorporate all the safety features necessary to adequately support the sign for its intended use and purpose and to protect UNO. Fabricator shall also be responsible for ensuring that all signs meet local, state and federal codes.

C. Vandalism Design

Fabrication and installation design is to withstand severe abuse and souvenir theft vandalism, but not less than the equivalent of resisting simple hand implements and tools (screwdrivers, knives, coins, keys, and similar items), and adult physical force. All hardware and fasteners within reach shall be vandal resistant.

D. Substitution

No substitution will be considered unless UNO has received written request for approval. Fabricator may recommend equal or better equipment or method, but will be required to provide full documentation establishing such a substitution's equality or superiority as measured in the following:

- compliance with the visual design intent;
- cost;
- ease of maintenance; and
- performance.

The burden of proof of the merit of the proposed substitute is upon the Fabricator. UNOs decision of approval or disapproval of a proposed substitution shall be final.

E. Material Handling

The Fabricator is to pack, wrap, crate, bundle, box, bag, or otherwise package, handle, transport, and store all fabricated work as necessary to provide protection from damage by every cause. Fabricator shall provide clear and legible identifying information on all product packaging to ensure proper on-site identification and installation.

F. Sign Specifications: Construction Methodology

The drawings call for a variety of fabrication techniques. Fabricators are given leeway to fabricate the signs to meet the intent of the designs depicted by the drawings.

1. Because different systems of extrusions may result in slightly different dimensional requirements, the total height and width dimensions described in the sign construction on the drawings may be considered “nominal” for the purposes of cost quote.

2. Sign faces are to be fabricated using aluminum plate of varying thicknesses, as specified on design intent drawings, with a minimum thickness of .125" unless otherwise noted.

3. Unless otherwise noted on the design intent drawings, all cut-out push-through copy is to be routed from a single sheet of white acrylic, with a minimum thickness of 3/8" and pushed through 1/16". Routed letters and shapes that are bonded to a separate acrylic sheet are not acceptable; they must be routed from a single sheet.

- Acrylic is to be attached to the back of the sign using adhesive, mechanical fasteners, or both depending on the design specifications.

- All letter knock-outs (interior of letter forms) are to be stud mounted through the acrylic.

- When illuminating the acrylic face with Fluorescent or Neon, 7328 shall be the standard white acrylic.

- When illuminating the acrylic face with LED, 2447 shall be the standard white acrylic.

- Acceptable spacing between the push-through acrylic and the cut-out aluminum is 1/32" to 1/16" depending on the copy height (if the copy is larger than 32", alternate spacing may be used to allow for the change in material expansion).

4. Sign cabinet seams shall be sealed to ensure they are watertight.

5. All finishes are to be satin finish, free from fading, peeling or cracking. Paint preparation of all exterior metal surfaces of the sign to include removal of all scratches and imperfections, sanding and chemical etching. Substrate cleaning, preparation, paint application and paint thickness to be in strict compliance with Matthews Paint or AkzoNobel published recommendations. Acceleration of the drying process is not allowed. Clear final top coat is required

6. Except where approved otherwise by UNO, conceal fasteners.

7. Any sign faces smaller than 8' by 20' are to be fabricated from 1 piece of seamless material.

8. On welded joints, dimensional and structural welding defects will not be accepted, including but not limited to: poor weld contours, including excessive bead convexity and reinforcement, and considerable concavity or under-sized welds; cracks; undercutting; porosity; incomplete fusion; inadequate penetration; spatter; and non-metallic inclusions. Welding is to be performed by AWS (or similar) certified personnel, following AWS Standard Welding Procedure Specifications (SWPSs) for steel, aluminum, and stainless steel as appropriate.

9. Non-welded joints between various portions of signs must have a tight, hairline-type appearance, without gaps. Provide sufficient fastenings to preclude looseness, racking, or similar movement.

10. Provide drain holes as needed to prevent accumulation of water within signs. Holes must be inconspicuous and be in inconspicuous locations; holes must be located such that drainage does not occur onto signs, or other surfaces subject to staining. Provide internal system of baffles to prevent “light leaks” through drain holes of illuminated signs. Provide color-coordinated insect screening over drain holes.

11. Non-illuminated sign faces are to have lettering and graphics created as silk-screening or as surface-applied vinyl typography using Oracal exterior grade, minimum 5-year warranty, as noted in the design intent drawings.

12. Visible metal joints must adhere to a fit tolerance of .01".

13. Unlit channel letter faces must be .25" aluminum. Channel letter returns must be .080" aluminum.

G. Sign Specifications: Illumination & Electrical

It shall be the responsibility of the Fabricator to perform the complete electrical design for illuminated signs. Illuminated signs shall be designed by an electrical engineer and shall be fabricated and wired to be compliant with current UL listing requirements, and shall be UL certified.

1. All internally illuminated sign cabinets are to have an access panel that is tight fitting, lightproof and water-proof. Access panels are to be in an accessible location, out of sight, and shall be shown on shop drawings.

2. Internally illuminated signs are to have an adequate internal system of ventilation to assure a uniform dissipation of heat from electrical components of electrically powered and illuminated signs, heat (solar) absorption by sign and other sources. Any openings in exterior surfaces

must be internally baffled to prevent light leaks and prevent entry of rain, snow, wind-blown debris, and other foreign matter, and are to be covered with interior color-coordinated insect screen.

3. Only labels required by law are permitted to be mounted on the exterior of the sign face, and they shall be located in a position that is as discreet as possible.

4. All internally illuminated interior metal surfaces shall be painted white using Matthews’ reflective white paint, or shall be lined with 3M’s Matte White Light Enhancement Film, to enhance and evenly distribute light.

5. All electrical components shall be built to be housed within sign cabinets. All wiring and raceways within the sign are to be completely enclosed. Internal illumination by LED is required to provide adequate and even illumination over the face of the sign without hot spots or shadows. “Halo” effects, “spreading” or similar light spill due to excessive transmission of the backlight source shall be minimized.

6. Illumination to be provided by LED as specified on design intent drawings. Internal hardware must not be visible through the translucent letterforms and graphics.

7. All internally illuminated exterior signs are to have their own electric eye on/off control to turn the sign on at night and off in the morning, unless UNO specifies a need for a timer. Location of eye to be shown on shop drawings.

8. Verify location of power provided by others prior to sign fabrication.

9. Face-lit channel letters with a 16" or shorter cap height shall be trimless. Face-lit channel letters taller than 16" may use a low-profile trim cap. Internally illuminated channel letters shall be illuminated using LED, unless otherwise noted on the design intent drawings. Transformers for channel letters shall be remote transformers wherever possible. If remote transformers are not applicable, then all electrical components shall be contained within the channel letter itself. Raceways are not acceptable unless specifically noted on the design intent drawing or if approved by UNO. All raceways must be painted the same color as the wall on which the sign will be mounted. Channel letters to be painted on the inside with Matthews’ reflective white paint, or lined with 3M’s Matte White Light Enhancement Film to enhance and evenly distribute light.

FABRICATION SPECIFICATIONS: EXTERIOR SIGNAGE

I. Fonts/Typefaces

The fonts used for this project were selected specifically for this project by UNO, and include those listed in the graphic standards. It is the responsibility of the fabricator to purchase the fonts.

No substitution of any other typefaces may be made. Under no circumstances are typefaces to be electronically distorted (“squeezed” or “extended”) for purposes of fitting to the specified sign or general alteration of the sign face composition unless noted in the drawings. This includes (but is not limited to) stretching, squeezing, tilting, outlining or shadowing.

1. All letterforms, symbols or graphics shall be reproduced either by photographic or computer-generated means. Hand-cut characters are not acceptable. Cutting shall be done in such manner that edges and corners of finished letterforms will be sharp and true. Letterforms with nicked, cut, ragged, rounded corners, and similar disfigurements will not be acceptable.

2. All letterforms shall be made from material and gauge as indicated on design intent drawings. Typefaces shall be replicated as indicated on the drawing.

3. Ligatures are to be turned off.

4. Apostrophes are to be used, not footmarks. Note that there is a difference in most fonts.

5. Silk-screened and vinyl copy is to match the sheen of the copy panel background (satin). Edges of letters shall be straight and corners sharp. Surface of letters shall be uniform in color finish, and free from pinholes and other imperfections.

6. Silk-screened images shall be executed with photo screens prepared from original art. No hand-cut screens will be accepted. Original art shall be defined as artwork that is a first generation reproduction of the specified art.

7. Silk-screening shall be highest quality, with sharp lines and no sawtooths or uneven ink coverage. Screens shall be photographically produced. Application of inks through screens shall consist of one flood pass and one print pass. Images shall be uniform in color and ink thickness. Images shall be free from squeegee marks and lines resulting from improper print stroke or screen off contact height. Signs shall be placed in adequate drying racks with minimum of 2 inches between racks for ample airflow. Sign racks shall have system of forced airflow between layers to provide proper drying and curing of inks. After signs have dried completely according to the ink manufacturer’s time allowance, signs may be packaged.

8. The edges and corners of routed letterforms shall be sharp and true. Letterforms with nicked, cut, ragged, rounded (positive or negative) corners, and similar disfigurements will not be acceptable.

9. Letterforms shall be aligned so as to maintain a base line parallel to the sign format, with margins and layout as indicated on design intent drawings and approved shop drawings. Vertical strokes shall be plumb.

10. Vinyl graphics and letterforms shall be computer-cut.

J. Permits and Variances

Fabricator shall be knowledgeable of relevant local code requirements and honor same in fabrication and installation. Where applicable, it is the responsibility of the Fabricator to secure any and all necessary permits for signage installation. It is the responsibility of UNO to secure variances, should any be required. It is UNO’s responsibility to call the appropriate agency to have all underground utilities properly located and marked. Any damage to below-grade utilities or structures for which UNO has provided adequate location information is the responsibility of the Fabricator.

K. Site Visit

Prior to installation of the signs, the Fabricator is to visit the proposed sites to observe existing conditions and verify all signage required and its location with UNO. At this time the locations shall be staked using a non-permanent visible device such as spray chalk or non-permanent visible device such as spray chalk or non-permanent visible device. Certain signs may be located on sloped grades and may require uneven footings for each post. Site-verify all locations to determine special requirements for footing templates, if required.

The final Sign Message Schedule and Sign Location Plan shall be consulted together and shall be approved by UNO to determine the precise location for each sign. Any necessary adjustments will be made with the approval of UNO.

L. Masonry/Footings

Any concrete bases for signage are to be poured in place and footings are to extend beneath the frost line, or deeper to meet local code. All footings or bases should be poured within a form and level with grade unless otherwise specified in the design intent drawings. Foundation/footings should be level with grade unless otherwise noted or as specified by state or local code. Foundation/footings should not extend above grade more than 2" and exposed edges should be finished with a bevel to prevent chipping. It’s recommended that the concrete be floated by machine or hand before finishing in order to embed larger aggregates especially when part of the footing or base extends above

ground. Concrete surface should have a smooth or brushed finish grade appearance. All concrete bases and footings should be edged to break any bond with the form and create a neat appearance. All forms should be removed once the concrete has properly cured. Concrete and reinforcement specifications shall be shown on shop drawing submittals. The Fabricator is responsible for the necessary templates, mounting plates and hardware for concrete and masonry bases. A minimum 1’ rock bed with landscape edging or concrete pad must be added around each concrete base as protection from landscaping maintenance.

All masonry (concrete block, poured concrete, brick, slab, veneer, mortar, etc.) is to be properly treated and protected to maintain the structural integrity of the masonry work with exposure to all environmental conditions found at the site. For exposed or visible masonry, this shall include the application of protective sealers or similar finishes to diminish the effects of close-proximity sprinkling or irrigation systems.

Signs are to be mounted on J-bolt footings, centered on the concrete base or footing, and engineered per code, unless otherwise specified in the design intent drawings.

M. Wind Load

Signs, banners and mounting devices shall be engineered to withstand a minimum 30-psf wind load normal to the sign, or greater as per local code, in addition to the weight of the sign. The Fabricator shall determine appropriate method of anchoring signs to the locations specified to meet these requirements as well as all local code requirements.

N. Mounting

All signs are to be mounted level and true. All exposed hardware is to be touch-up painted on site as required. It is preferred that all bolts, nuts, washers, or other fasteners be stainless steel. However galvanized steel is acceptable, so long as all exposed surfaces are sealed.

While sign type drawings may specify or indicate possible mounting and/or mounting hardware details, the Fabricator will be able to substitute equal or better hardware and techniques, based upon their experience with similar mounting situations and as long as the visual appearance of the sign is not compromised from that shown in the design intent drawings.

All signage products must be installed such that there are no misalignments between visible components. Sign elements intended to be removable or changeable after installation must function as intended without binding, sticking or blocking. It will be the responsibility of the Fabricator to correct any installation misalignments at no charge.

Fabricator and their installers are expected to have knowledge of ADA mounting guidelines and city zoning codes, general sign locating practices, and any particular unique installations defined by UNO. It is the desire of UNO that the Fabricator follow these guidelines as well as architectural cues in installing for the best visual placement, keeping a reasonable distance from protruding objects. Any signage that is improperly located is to be moved to the proper location by the Fabricator, and repairs to wall surfaces and signage are to be completed at the Fabricator’s expense.

If the installers are unable to make a decision about any sign locations, they can contact UNO, providing a graphic representation of the questionable area, or for on-site options.

O. Electrical

UNO will be responsible for providing a power source to within 10 feet of the base of each sign requiring power (either at grade or below grade). Power is to be 120 or 277 (LED illumination should be 120) volts at 60 cycles unless otherwise noted in the documents. It is the responsibility of the Fabricator to manipulate the existing conduit to its proper location, install an external disconnect, extend the conduit through the concrete base (or posts) to align with the point of hookup, and run the power supply through it. Conduit running from the disconnect to the sign shall travel within the concrete base, not on its surface. The Fabricator will be responsible for the final electrical connection.

P. Punchlist

It is required that the successful Bidder complete a walk through with UNO immediately following installation to identify any errors, such as construction or installation issues. Such errors are to be corrected in a timely manner, and to the satisfaction of UNO.

Q. Site Safety and Restoration

During the installation period, successful Bidders and subcontractors are responsible for their own safety, and are expected to maintain a safe environment for pedestrians. Successful Bidders and subcontractors are to keep UNO’s premises and the adjoining premises, driveways and streets clean and clear. Job site shall be left safe, neat and clean at the completion of each day’s operation. Successful Bidders and subcontractors are also expected to temporarily maintain old signs in order to continue their directional and identification functions, as well as to maintain signage that meets MUTCD standards during the installation period. At the completion of work, successful Bidder and subcontractors shall remove all rubbish, tools, equipment, and surplus materials, from and about the premises, and shall leave the site as originally found. Successful Bidder shall be responsible for repairing or correcting damage to other contractors’ work resulting from successful Bidder’s work.

FABRICATION SPECIFICATIONS: EXTERIOR SIGNAGE

R. Signage Warranty

The successful Bidder is to provide a written five (5) year full replacement warranty to UNO that all signs will be free of defects due to craft work including, but not limited to:

1. Bubbling, chalking, rusting or other disintegration of the sign panel, graphics or of the edges.
2. Corrosion appearing beneath paint and vinyl surfaces, on sign panels, brackets, posts or other support assemblies (except as an obvious result of vandalism or other external damage).
3. Corrosion of fasteners.
4. The assemblies not remaining true and plumb on their supports.
5. Peeling, delamination or warping (“oil canning”).
6. Repair and reinstallation of signage due to failed mountings.

Successful Bidder shall also extend in writing to UNO all manufacturers’ warranties for materials and components used within the signs. It is the Successful Bidder’s responsibility to obtain extended 5-year manufacturer warranties on all paint and powder coat applications.

S. Repair or Replacement

Without additional cost to UNO, the successful Bidder shall repair or replace, including installation, any defective signs or hardware which develop during the warranty period and repair any damage to other work due to such imperfections. The successful Bidder will be required to fully replace all signs that are in error relative to the working documents (sign message schedule and sign type drawings) that will be submitted to the successful Bidder upon award of contract.

T. Pre-fabrication Submittals

Upon award of contract, the successful Bidder must submit a copy of the following items to UNO for their review prior to fabrication of the prototypes and rest of the fabrication package:

1. Detailed engineered shop drawings for each sign type are to be submitted as electronic PDF no larger than 11”x 17”. Final Shop Drawings are to be stamped by an Engineer licensed in the State of Nebraska. The shop drawings for each sign type shall illustrate/describe the following:

i. Elevations and cross sections – front, sides, top and back (if necessary); side sections; internal structure section/details; enlarged details such as of extrusions, push-through letter mounting, mounting plate, etc.; with all final dimensions and call-outs for:

- Components – construction details/information related to individual elements
- Materials – color, type, gauge, and thickness (including substrates and overlays)
- Finishes – color, type of product, manufacturer, and sheen
- Fonts, graphics specifications and message fields

ii. Exploded view (optional) – isometric view with components, materials, and finishes.

iii. Cross-section of corners – one illustration for each corner condition. Items to be illustrated: seams, joints, layers, internal support and fasteners.

iv. Mounting/installation details – provide foundation cross-sections (including hardware), bracket/post details, elevations, materials, finishes and fasteners.

v. Electrical details are to be provided for all elements that require electricity. Specific items to be listed are:

- Light source and/or fixture type and manufacturer
- Power supply (transformer)
- Amperage and voltage per sign
- Electrical service required (source)
- Lighting detail – provide an internal view of light fixtures, LED layout, transformers, external cut-off switch, light sensor, and timer.

vi. Engineering for wind load

vii. Removable panels (where applicable)













viii. Identify any dimensional or other changes in the overall sign required by virtue of the fabrication materials, techniques and/or engineering.

2. Two (2) samples of each material (paint, vinyl, acrylic, veneer, masonry, metal, etc.) to be used on the sign using actual substrate materials. One sample will be returned, one sent to UNO.

3. A proofing document of final production keystroking for all sign messages to verify line breaks, character and word spacing, and interline spacing. The proofs are to be scaled production art files, not full sized. Each layout is to be identified with the sign number.

MATERIALS AND FINISHES

Fabricator is responsible for supplying samples for all colors within the palette.

						
	01 Concrete	02 Metallic Silver	03 Dark Grey	04 White	05 Red	06 Black
Matthews Paint:	---	MP18128 Saab Silver Metallic	MP42359 Vine Charcoal	MP27386 Verizon White	MP00225 Rose Petal	MP33764 Black Indigo
Exterior grade vinyl:	---			Oracal 851 Premium Cast 010 white Oracal 5700 engineer grade reflective vinyl 010 White	Oracal 851 Premium Cast 032 Light Red	---
						
	07 Light Grey	08 Light Blue	09 Green	10 Traffic Blue	11 Grey	12 High Intensity Reflective White
Matthews Paint:	MP02650 Garbo Silver	---	---	---	---	---
Exterior grade vinyl:	---	Oracal 851 Premium Cast 053 Ice Blue	Oracal 8300 Transparent Cal 061 Green Oracal 851 Premium Cast 062 Light Green	Oracal 8300 Transparent Cal 057 Traffic Blue Oracal 851 Premium Cast 509 Sea Blue	Oracal 8300 Transparent Cal 074 Middle Grey	ORALITE series 5800 High intensity reflective sheeting

TYPOGRAPHY (Editable)

Fabricator is responsible for acquiring project related fonts.

Gotham - Book

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

Gotham - Medium

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

Gotham - Bold

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

Gotham Condensed - Book

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890


Gotham Condensed - Medium

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890


Helvetica Neue - Medium

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

LOGOS AND SYMBOLS




UNO academic icon




UNO academic icon with white background




UNO system logo




Information



Parking



Guide arrow



Guide arrow (alternate)



Handicapped Parking



Accessible entrance



No Smoking

Sign Type

Materials, Finishes, Logos and Symbols

Fabricator is responsible for matching all colors and materials as specified and are required to provide color and material samples to UNO for approval.

CAUTION!
CONSISTENT AND ACCURATE COLOR REPRODUCTION IN THIS DOCUMENT CANNOT BE ASSURED DUE TO THE LIMITATIONS OF COLOR COPYING TECHNOLOGY.

The Coated Pantone Matching System®, Matthews and/or Akzo Nobel Paint system is used for specifying signage color matches. (In the absence of actual sign material color chip reference sets, actual specified product color swatches should be referenced for color matching.)

Shown here are approximations of the primary signage background colors and supporting accent colors. Actual color finishes on signage must be matte or low luster (not shiny or glossy unless otherwise noted) and exclusively a premium acrylic polyurethane.

Signage paints produced by MPC Matthews Paint and Akzo Nobel Paint Company are to be the standard reference.

Vinyl Films from 3M and Oracal Graphics are to be the standard.

Color application varies per sign type. Refer to drawings for appropriate application.

Date	Description
02.01.12	DESIGN INTENT




Client

University of
Nebraska at Omaha



corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Cx-1a Dodge Campus Identifier-Retrofit with LED Display

Scale

1/2" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description


11.09.11 Design intent

Client



University of Nebraska at Omaha

corbindesign


109 East Front Suite 304
Traverse City, MI 49684
231 947.1236




Logo Option 1




Logo Option 2



Sign Type	
UNO Prototype Icon Logo Details	
Scale	
1/2" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
11.09.11	Design intent
04.30.12	Design Intent
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	



Sign Type

Cx-1b 
Pacific Campus Identifier-
Retrofit with LED Display

Scale

1/2" = 1'-0"

Color Code

Notes


This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision


Client




University of
Nebraska at Omaha



corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236





Sign Type

Cx-1c 
Pacific Campus Identifier
NEW SIGN BASE AND
FOUNDATION

Scale

1/2" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision


Client

University of
Nebraska at Omaha

>

corbindesign


109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Top view



Night view



Sign Location D020




Sign Location D090



Sign Location D085

Sign Type

Cx-2a 
Campus Identifier-
Retrofit

Scale

1/2" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

Date	Description
06.03.11	Prototype design intent
09.14.11	Revision


Client

University of
Nebraska at Omaha


>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Top view



Night view



Sign Type

Cx-2b 
Center Campus Identifier
NEW BASE AND
FOUNDATION

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision


Client




University of
Nebraska at Omaha

>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236





Sign Type

Dx-1 ★
Pedestrian Map Kiosk
(Large)

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.



Date	Description
11.09.11	Design intent

Client


**University of
Nebraska at Omaha**

corbindesign


109 East Front Suite 304
Traverse City, MI 49684
231 947.1236





Message layouts




Removable map panel detail




Sign Type	
Dx-2 ☆ Vertical Pedestrian Building Identifier with Map	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
11.09.11	Design intent
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Alternate trailblazer layout




Alternate guide layout



Alternate layouts



Sign Type	
Gx-1 Trailblazer	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
09.14.11	Revision
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	



Sign Type

Gx-2
Vehicular Guide
(6" text)

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description


06.03.11 Prototype design intent

Client

University of
Nebraska at Omaha

>
corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Gx-3 █
Vehicular Guide
(4" text)

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description



06.03.11 Prototype design intent

Client


**University of
Nebraska at Omaha**

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Gx-4 
Vehicular Guide with
Digital Message Board
(4" text)

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description


06.03.11 Prototype design intent



Client


**University of
Nebraska at Omaha**


corbindesign



109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type	
Gx-5  Vehicular Guide (4" text)	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
Client	
University of Nebraska at Omaha	
>	
	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Sign Type	
Gx-6  Pedestrian Guide	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
09.14.11	Revision
Client	
University of Nebraska at Omaha	
>	
corbindesign 109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	



SCOTT RESIDENCE
THOMPSON ALUMNI CENTER
SCOTT VILLAGE

Message Layouts




Sign Type
Ix-1b ■ Building Identifier- Retrofit
Scale
1/2" = 1'-0"
Color Code
Notes
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date	Description
06.03.11	Prototype design intent
09.14.11	Revision

Client

University of
Nebraska at Omaha



Sign Type

Ix-2 ■
Vertical Vehicular
Building Identifier

Scale

1/2" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.




Date	Description
11.09.11	Design intent

Client


**University of
Nebraska at Omaha**

corbindesign


109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Message layouts



Sign Type

Ix-3 
Vertical Pedestrian
Building Identifier

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date	Description
06.03.11	Prototype design intent
09.14.11	Revision


Client

University of
Nebraska at Omaha




corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Ix-4a 
Building Identifier,
Small Horizontal

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.


Date	Description
06.03.11	Prototype design intent

Client


**University of
Nebraska at Omaha**

corbindesign



109 East Front Suite 304
Traverse City, MI 49684
231 947.1236




Alternate layout 1



Alternate layout 2




Side view



Back view

Sign Type

Ix-4b  Building Identifier, Large Horizontal

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description


06.03.11 Prototype design intent

Client


University of Nebraska at Omaha

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Ix-5  **Parking Identifier**

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description




06.03.11 Prototype design intent

Client

University of Nebraska at Omaha

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Ix-6 ■
Parking Identifier with
Digital Message Board

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11 Prototype design intent



Client

**University of
Nebraska at Omaha**

>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

Ix-7 and Ix-7a 
Parking Identifier,
wall mounted

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision


Client

**University of
Nebraska at Omaha**





corbindesign


109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Plan view




Back view






Side view


Sign Type	
Ix-8 + Street Identifier	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
09.14.11	Revision
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Sign Type	
Ix-9 Building Identifier Wall Mounted	
Scale	
1/2" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
09.14.11	Revision
02.20.12	Added
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	



Sign Type	
Rx-1 and Rx-1a ◇ Regulatory	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
09.14.11	Revision
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	
36	



Front view



Front view

Sign Type

Rx-2 & Rx-2a ◇
Regulatory
Wall mounted

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision

Client

**University of
Nebraska at Omaha**




corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236




Temporary Message Layout




Front view

WindSign Available in 3 sizes

Assembles in less than 5 minutes



Sign frame and spring are easily assembled with the provided hardware. Only a screwdriver is required. Wheels are factory installed. Instruction sheet included. Assembles in less than 5 minutes.



WindSign Dimensions:

WindSign: 32.75"h x 24"w x 2.5"d
(40"h x 26"w on base assembly)
weight: 11 lbs.

WindSign II: 40.75"h x 26"w x 2.5"d
(48"h x 26"w on base assembly)
weight: 12 lbs.



WindSign III: 44.75"h x 30"w x 2.5"d
(53"h x 30"w on base assembly)
weight: 16.7 lbs.

Base: 4.5"h x 26"w x 18"d
weight: 4.3 lbs.
(90 lbs. filled with sand)
(45 lbs. filled with water)

Each sign frame displays two signs.



Molded-in handle and factory installed wheels assure easy mobility.



MADE IN THE USA
US PATENT 7,337,569

PLASTICADE PRODUCTS

7700 Austin Avenue
Skokie, IL 60077
phone (800) 772-0355
fax (847) 966-8074
www.plasticade.com

Sign Type

Tx-1
Temporary

Scale

3/4" = 1'-0"

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

06.03.11	Prototype design intent
09.14.11	Revision


Client

**University of
Nebraska at Omaha**


>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236




Vx-1 Front view



Vx-1a Front view

Sign Type	
Vx-1 and Vx-1a ✖ Vinyl on Glass	
Scale	
3/4" = 1'-0"	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
06.03.11	Prototype design intent
09.14.11	Revision
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	


INTERIOR DESIGN ARRAY



D-1
Directory, Building

- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert

Building Directory
This sign type lists the building name and level, and displays a floor plan of the building along with the location of public corridors, building destinations and amenities. The header element and colors reinforce the University of Nebraska at Omaha academic identity.




D-1a
Monitor Display Frame

- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Permanent painted aluminum background panel

UNO Branded Monitor Display Frame
This sign type surrounds with the building monitors. The frame and background convey UNO branding.


NOTE: Vertical format is the default standard for interactive monitors. See pages 49, 50 for more information.



D-2
Directory, Faculty

- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert


Directory Faculty
This sign type lists the building name and level, and provides the names and room numbers of faculty members whose offices are in the building.




G-1
Wall Guide, Large

- Construction Details:**
- APCO FullView, FV_3022(V)MF 22"(w) x 30"(h)
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert

Wall Guides
These sign types are located at key intersections and along major pathways to direct to nearby destinations and amenities while the header element and colors reinforce the University of Nebraska Omaha identity. A footer element on these signs types list the building name and level number. Destinations should be listed in the following order: left, then right, then straight ahead. Destinations within each direction grouping should be listed alphabetically.



G-3
Wall Guide, Acrylic



G-2
Wall Guide, Small

- Construction Details:**
- APCO FullView, FV_2222(V)MF 22"(w) x 22"(h)
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert

- Construction Details:**
- Acrylic window insert
 - Removable printed insert


INTERIOR DESIGN ARRAY

Construction Details:

- APCO FullView, FV_1411(V) 11"(w) x 14"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert and tactile and Braille panel



I-1
Primary Department Identifier




I-1a
Room Monitor
Display Frame

Construction Details:


- APCO FullView, large format acrylic display
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Permanent painted aluminum background panel

Department, Room, Office and Regulatory Identifiers

These sign types are used to indicate the location of public destinations. The largest version of this sign type can also list other information such as hours of operation. Some of the sign types can also incorporate a notifier bar to hold temporary paper inserts. A footer element on most of the signs presents the room number in tactile lettering and Braille, as required by the Americans with Disabilities Act.



I-2
Room Identifier, Large



I-2a
Room Identifier,
Large - w/ notifier bar

Construction Details:

- APCO FullView, FV_1485(V) 8 1/2"(w) x 14"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert and tactile and Braille panel



I-3
Room Identifier, Small



I-3a
Room Identifier,
Small - w/ notifier bar

Construction Details:


- APCO FullView, FV_1185(V) 8 1/2"(w) x 11"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert and tactile and Braille panel



I-4
Room Number
Identifier



I-4a
Room Number
Identifier - w/ notifier bar




I-4b
Door Frame Number
Identifier




I-4c
Room Name &
Number Identifier

Construction Details:

- Acrylic sign w/ tactile and Braille panel



I-5
Office Identifier
Identifier




I-5a
Office Identifier
Identifier - w/ notifier bar


Construction Details:

- APCO FullView, FV_8585(V) 8 1/2"(w) x 8 1/2"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert and tactile and Braille panel

INTERIOR DESIGN ARRAY



O-1
Projecting Overhead Identifier




O-2
Overhead Guide and Identifier

Construction Details:
-APCO FullView, FV_1248(V) 12"(w) x 48"(h)
- CMF and CMW, double-sided
- Natural Satin Anodized contour FVST-6

Overhead Signs
These sign types should be used on a limited basis where the line of sight is an important issue.

Insert Notice Frames
These sign types are used whenever notice or regulatory information needs to be posted and changed regularly. Two sizes allow the printing and use of letter or tabloid-sized paper inserts.




I-6
Office/Cubicle Identifier Identifier, Small



I-6a
Office/Cubicle Identifier Identifier, Small - w/ notifier bar


Construction Details:
-APCO FullView, FV_5585(V) 8 1/2"(w) x 5 1/2"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized
-Removable acrylic window and printed insert




R-1
Regulatory

Construction Details:
-APCO FullView, FV_1185(V) 8 1/2"(w) x 11"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized
-Removable acrylic window and printed insert and tactile and Braille panel

T-1
Freestanding Temporary Insert




Construction Details:
-APCO FullView, FV_1711(V) 11"(w) x 17"(h)
- FS300 series vertical insert, double-sided
- Natural Satin Anodized




N-1
Insert Notice

Construction Details:
-APCO FullView, FV_1185(V) 8 1/2"(w) x 11"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized




N-1a
Insert Notice

Construction Details:
-APCO FullView, FV_8511(V) 11"(w) x 8 1/2"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized



N-1b
Insert Notice

Construction Details:
-APCO FullView, FV_1711(V) 11"(w) x 17"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized



N-1c
Insert Notice

Construction Details:
-APCO FullView, FV_1117(V) 17"(w) x 11"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized

FABRICATION SPECIFICATIONS: INTERIOR SIGNAGE

A. Quality Standards

The materials, products, equipment and performance specifications described within establish a standard of required function, dimension, appearance, performance and quality to be met by the Fabricator.

B. Structural Design

Details on design intent drawings indicate a design approach for sign structure but do not necessarily include all fabrication details required for the complete structural integrity of the signs, including consideration for static, dynamic and erection loads during handling, erecting, and service at the installed locations, nor do they necessarily consider the preferred shop practices of the Fabricator. Therefore, it shall be the responsibility of the Fabricator to perform the complete structural design and engineering of the signs and to incorporate all the safety features necessary to adequately support the sign for its intended use and purpose and to protect UNO. The Fabricator shall be responsible for ensuring that all signs meet local, state, and federal codes.

C. Vandalism Design

Fabrication and installation design is to withstand severe abuse and souvenir theft vandalism, but not less than the equivalent of resisting simple hand implements and tools (screwdrivers, knives, coins, keys, and similar items), and adult physical force. All hardware and fasteners within reach shall be vandal resistant.

D. Substitution

No substitution will be considered unless UNO has received written request for approval. Fabricator may recommend equal or better equipment or method, but will be required, prior to a quote submittal, to provide full documentation establishing such a substitution’s equality or superiority as measured in the following:

- Compliance with the visual design intent;
- cost;
- ease of maintenance; and
- performance.

The burden of proof of the merit of the proposed substitute is upon the Fabricator. UNO’s decision of approval or disapproval of a proposed substitution shall be final.

E. Material Handling

The Fabricator is to pack, wrap, crate, bundle, box, bag, or otherwise package, handle, transport, and store all fabricated work as necessary to provide protection from damage by every cause. Fabricator shall provide clear and legible identifying information on all product packaging to ensure proper on-site review and installation.

F. Construction Methodology

The drawings call for a variety of fabrication techniques. Fabricators are given leeway to fabricate the signs to meet the intent of the designs depicted by the drawings.

Because different systems of extrusions may result in slightly different dimensional requirements, the total height and width dimensions described in the sign construction on the drawings may be considered “nominal” for the purposes of pricing.

1. All finishes are to be satin finish, free from fading, peeling or cracking. Paint preparation of all exterior metal surfaces of the sign to include removal of all scratches and imperfections, sanding and chemical etching. Substrate cleaning, preparation, paint application and paint thickness to be in strict compliance with Matthews Paint or AkzoNobel published recommendations. Acceleration of the drying process is not allowed.

2. Except where approved otherwise by UNO, conceal fasteners.

3. On welded joints, dimensional and structural welding defects will not be accepted, including but not limited to: poor weld contours, including excessive bead convexity and reinforcement, and considerable concavity or undersized welds; cracks; undercutting; porosity; incomplete fusion; inadequate penetration; spatter; and non-metallic inclusions. Welding is to be performed by AWS (or similar) certified personnel, following AWS Standard Welding

Procedure Specifications (SWPSs) for steel, aluminum and stainless steel as appropriate.

4. Non-welded joints between various portions of signs must have a tight, hairline-type appearance, without gaps unless a reveal dimension has been called for or approved. Provide sufficient fastenings to preclude looseness, racking, or similar movement.

5. Non-illuminated inserts will minimally be printed at 1200 DPI using pigment-based UV inks on a white, satin finish UV-coated photo paper, with a matte UV over-laminate (unless otherwise noted in the design intent drawings). The thickness of the photo paper must be heavy enough such that no wrinkles or waves will occur once installed into the sign housings. If necessary, rigid backers may be used. All paper inserts to be produced by UNO unless specifically stated in bid documents.

6. For sign types required to sit behind a non-glare front lens or “window”, this window must be of not greater thickness than 0.100” and must be a premium non-glare product equal to or exceeding Calsak Acrycast LX cast acrylic sheet, free from surface imperfections or ripples.

7. All enclosures or housings of message inserts must have fabrication tolerances such that the message inserts touch or remain not more than 1/32” from the inside face of the window.

8. Any insert designed for a given sign type must fit properly into all same sign types.

9. It will be the Fabricator’s responsibility to generate all messages, including necessary tactile and Grade 2 Braille, from the message schedule. UNO will not produce graphic files for all sign messaging.

G. Fonts/Typefaces

The fonts used for this project were selected specifically for this project by the UNO, and include those listed in the graphic standards. It is the responsibility of the fabricator to purchase the fonts.

No substitution of any other typefaces may be made. Under no circumstances are typefaces to be electronically distorted (“squeezed” or “extended”) for purposes of fitting to the specified sign or general alteration of the sign face composition unless noted in the drawings. This includes (but is not limited to) stretching, squeezing, tilting, outlining or shadowing.

1. All letterforms, symbols or graphics shall be reproduced either by photographic or computer-generated means. Hand-cut characters are not acceptable. Cutting shall be done in such manner that edges and corners of finished letterforms will be sharp and true. Letterforms with nicked, cut, ragged, rounded corners, and similar disfigurements will not be acceptable.

2. All letterforms shall be made from components, material and gauge as indicated on design intent drawings. Typefaces shall be replicated as indicated on the drawing.

3. Ligatures are to be turned off.

4. Apostrophes are to be used, not foot marks. Note that there is a difference in most fonts.

5. Silk-screened and vinyl copy is to match the sheen of the copy panel background (satin). Edges of letters shall be straight and corners sharp. Surface of letters shall be uniform in color finish, and free from pinholes and other imperfections.

6. Silk-screened images shall be executed with photo screens prepared from vector art files. No hand-cut screens will be accepted. Original art shall be defined as artwork that is a first generation reproduction of the specified art.

7. Silk-screening shall be highest quality, with sharp lines and no sawtooths or uneven ink coverage. Screens shall be photographically produced. Application of inks through screens shall consist of one flood pass and one print pass. Images shall be uniform in color and ink thickness. Images shall be free from squeegee marks and lines resulting from improper print stroke or screen off contact height. Signs shall be placed in adequate drying racks with minimum of 2 inches between racks for ample airflow. Sign racks shall have system of forced airflow between layers to provide proper drying and curing of inks. After signs have dried

completely according to the ink manufacturer’s time allowance, signs may be packaged.

8. Electronic templates for all sign types shall be supplied to UNO by the successful Bidder, thus allowing UNO to reproduce paper inserts as needed. UNO shall also receive training from the successful bidder on using the templates to insure consistent quality and adherence to standards in insert production. Templates are to be created in a PC compatible format, using either a common off the shelf program such as Microsoft WORD or Adobe Illustrator, or proprietary software that the successful Bidder will supply UNO and instruct them on how to use the program as part of the installation package.

9. All tactile and Grade 2 Braille characters are to be created using the photopolymer or raster dot method as dictated by ADA code requirements.

H. Site Visit

Prior to installation of the signs, the Fabricator is to visit the proposed site to observe existing conditions and verify all signage required and its location with UNO/General Contractor. Site-verify all locations to determine special requirements. The Fabricator must contact UNO prior to the start of installation to coordinate with other trades performing work on site.

The final Sign Message Schedule and Sign Location Plan shall be consulted together and shall be approved by UNO to determine the precise location for each sign. Any necessary adjustments will be made with the approval of UNO.

I. Mounting

All signs to be mounted level and true, and within the guidelines of the Americans with Disabilities Act (ADA) and other local codes, where applicable. All exposed hardware is to be touch-up painted on site as required.

While sign type drawings may specify or indicate possible mounting and/or mounting hardware details, the Fabricator will be able to substitute equal or better hardware and techniques, based upon their experience with similar mounting situations and as long as the visual appearance of the sign is not compromised from that

shown in the design intent drawings, and as long as it does not require that exposed surfaces or structure of the architectural space (that may have been prepared for signage) be redone.

All signage products must be installed such that there are no misalignments between visible components. It will be the responsibility of the Fabricator to correct any installation misalignments at no charge.

It is the responsibility of the Fabricator to work with UNO to review all sign locations and ensure that every location has the necessary blocking for safe and secure mounting. Where additional blocking is needed, the Fabricator is responsible for recommending changes and additional associated costs, and is to receive approval prior to beginning installation.

Fabricator and their installers are expected to have knowledge of ADA mounting guidelines and other applicable local codes, general sign locating practices, and any particular unique installations defined by UNO. It is UNO’s desire that the Fabricator follow these guidelines and regulations as well as architectural cues in installing for the best visual placement, keeping a reasonable distance from protruding objects. Any signage that is improperly located is to be moved to the proper location by the Fabricator, and repairs to wall surfaces and signage are to be at the Fabricator’s expense.

If the installers are unable to make a decision about any sign locations, they can contact UNO, providing a graphic representation of the questionable area, or for on-site options.

J. Punch List

It is required that the Fabricator complete a walk through with UNO immediately following installation to identify any errors, such as construction or installation issues. Such errors are to be corrected in a timely manner, and to the satisfaction of UNO.

K. Warranty

The Fabricator is to provide a written five (5) year full replacement warranty to UNO that all signs will be free of defects due to craft work and materials including, but not limited to:

- Assemblies not remaining true and plumb on their supports, mountings giving way or loosening, and separation of components;
- Fading and discoloration of the colors and finishes within the vinyl and paint manufacturer’s stated warranty period;
- Peeling, delamination or warping (“oil canning”); and
- Repair and reinstallation of signage due to failed mountings.

Fabricator shall also extend in writing to UNO all manufacturers’ warranties.

L. Repair or Replacement

Without additional cost to UNO the Fabricator shall repair or replace, including installation, any defective signs or hardware that develop during the warranty period and repair any damage to other work due to such imperfections. The Fabricator will be required to fully replace all signs that are in error relative to the working documents (sign message schedule and sign type drawings) submitted to the Fabricator upon award of contract.

M. Pre-fabrication Submittals

Upon award of contract, the successful Bidder must submit a copy of the following items to UNO for their review prior to fabrication of the prototypes and rest of the fabrication package:

1.Detailed engineered shop drawings for each sign type are to be submitted as electronic PDF no larger than 11”x 17”. Final Shop Drawings are to be stamped by an Engineer licensed in the State of Nebraska. The shop drawings for each sign type shall illustrate/ describe the following:

- i. Elevations and cross sections – front, sides, top and back (if necessary); side sections; internal structure section/details; enlarged details such as of extrusions, push-through letter mounting, mounting plate, etc.; with all final dimensions and call-outs for:
 - Components – construction details/information related to individual elements
 - Materials – color, type, gauge, and thickness (including substrates and overlays)
 - Finishes – color, type of product, manufacturer, and sheen
 - Fonts, graphics specifications and message fields
- ii. Exploded view (optional) – isometric view with components, materials, and finishes.
- iii. Cross-section of corners – one illustration for each corner condition. Items to be illustrated: seams, joints, layers, internal support and fasteners.
- iv. Mounting/installation details – provide foundation cross-sections (including hardware), bracket/ post details, elevations, materials, finishes and fasteners.

- v. Electrical details are to be provided for all elements that require electricity. Specific items to be listed are:
 - Light source and/or fixture type and manufacturer
 - Power supply (transformer)
 - Amperage and voltage per sign
 - Electrical service required (source)
 - Lighting detail – provide an internal view of light fixtures, LED layout, transformers, external cut-off switch, light sensor, and timer.

vi. Removable panels (where applicable)

vii. Identify any dimensional or other changes in the overall sign required by virtue of the fabrication materials, techniques and/or engineering.






2.Two (2) samples of each material (paint, vinyl, acrylic, veneer, masonry, metal, etc.) to be used on the sign using actual substrate materials. One sample will be returned and one kept in UNO’s records.

3.A proofing document of final production keystroking for all sign messages to verify line breaks, character and word spacing, and interline spacing. The proofs are to be scaled production art files, not full sized. Each layout is to be identified with the sign number.

GRAPHIC STANDARDS

MATERIALS AND FINISHED

Fabricator is responsible for supplying samples for all colors within the palette.

					
	01 Metallic Silver	02 Dark Grey	03 White	04 Red	05 Black
Matthews Paint:	Anodized Aluminum Finish MP18128 Saab Silver Metallic	MP42359 Vine Charcoal	MP27386 Verizon White	MP00225 Rose Petal	MP33764 Black Indigo
<p>Fabricator is responsible for matching all colors and materials as specified and are required to provide color and material samples to UNO for approval.</p> <p>CAUTION! CONSISTENT AND ACCURATE COLOR REPRODUCTION IN THIS DOCUMENT CANNOT BE ASSURED DUE TO THE LIMITATIONS OF COLOR COPYING TECHNOLOGY.</p>		<p>The Coated Pantone Matching System®, Matthews and/or Akzo Nobel Paint system is used for specifying signage color matches. (In the absence of actual sign material color chip reference sets, actual specified product color swatches should be referenced for color matching.)</p> <p>Shown here are approximations of the primary signage background colors and supporting accent colors. Actual color</p>		<p>finishes on signage must be matte or low luster (not shiny or glossy unless otherwise noted) and exclusively a premium acrylic polyurethane.</p> <p>Signage paints produced by MPC Matthews Paint and Akzo Nobel Paint Company are to be the standard reference.</p> <p>Vinyl Films from 3M and Oracal Graphics are to be the standard.</p>	
<p><i>Color application varies per sign type. Refer to drawings for appropriate application.</i></p>					

TYPOGRAPHY (Editable)

Fabricator is responsible for acquiring project related fonts.

Gotham - Book

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

Gotham - Medium

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

Gotham - Bold


Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

Gotham Narrow - Medium

Aa Bb Cc Dd Ee Ff Gg Hh Ii Jj Kk Ll Mm Nn Oo
Pp Qq Rr Ss Tt Uu Vv Ww Xx Yy Zz 1234567890

LOGOS AND SYMBOLS


Designer will provide vector artwork for all project related logos and symbols



UNO academic icon




UNO system logo




Guide arrow




Women barrier-free restroom




Men barrier-free restroom




Restroom




Barrier-free restroom



Women restroom




Men restroom



Stairs




Accessible Restroom



Elevator


MOUNTING GUIDELINES

The following signs are installed between 40" to 70" from the top of the sign to the floor. This places important wayfinding information at a standard reading level for all visitors.




ADA requires that tactile characters on a sign be mounted between 48" and 60" from the tactile character baseline to the floor. Mounting most wayfinding signs at 60" to the center of the sign is the optimal location for the average user to read and distinguish each sign clearly.

In the case where the door swings toward the visitor, signs must be installed a minimum of 9" from the center of the tactile message to the edge of the door. If the sign is more than 10" wide, install the sign a standard distance of 4" from the door frame, assuming that the 18" clear space is still met.




NOTE: The Mounting Guideline pages are provided as a reference only. These guidelines are an interpretation of the 2011 ADA Standards for Accessible Design, and are not to be construed as legal advice concerning compliance with any law or regulation.

The following public notice signs are installed 60" from the center of the sign to the floor.




ADA states that tactile room identification signs shall be installed on the latch side of the door (Illustration 1A). In the case of a double door, the sign shall be installed on the inactive leaf of the door (Illustration 1B). If both doors are active, then the sign is installed to the right

of the right hand door. If there is no space on the latch side of the door, or to the right side of the double doors, then the sign is to be installed on the nearest adjacent wall space (Illustration 1C).





Signs with tactile characters may be installed on the push side of a door (doors that open into the room, not into the circulation space), so long as the door has a closer and is not on a hold-open device.



For example, restroom doors that push open into the restroom, and the door automatically closes, may have the tactile identification sign installed on the door. (Illustration 2)

Note that tactile signs must be installed such that a clear floor space of 18 inches by 18 inches, centered on the tactile copy, is provided outside of the swing of a door. (Illustration 3A and 3B)






- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert

- Paper Details:**
- Printed at 1200 DPI using pigment-based UV inks
 - White, satin finish UV-coated photo paper with matte UV over-laminate
 - Thickness of paper to be heavy enough to prevent wrinkles or waves once installed


Sign Type	
D-1 Building Directory	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	











- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Permanent painted aluminum background panel

Sign Type	
D-1a Monitor Display Frame	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	

NOTE: Vertical format is the default standard for interactive monitors.



Offices/Services		(5.1:1) #906700
Classrooms/Labs		(11.6:1) #333366
Activity Areas		(6.1:1) #666600
Meeting Areas		(8.9:1) #622424
Study/Lounge		(5.3:1) #177A6C
RestRoom		#B19490
stair/elevator		#C2AD9C



Layouts and programming provided by Four Winds Interactive

Sign Type

Monitor Content Layout

Scale

not to scale

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

Client

University of
Nebraska at Omaha


>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236

All products on this page manufactured by APCO

Series 3200



Poster Displays

- Standard Insert Sizes
- ¥ 8-1/2" x 11" Landscape
- ¥ 11" x 17" Portrait
- ¥ 11" x 17" Landscape
- ¥ 22" x 22"

Literature Holders

Fully modular and adjustable to accomodate a wide range of brochure and pamphlet sizes or other materials.

Directories / Directionals

Featuring a range of modular, injection molded message strips

Custom Configurations


- ¥ Full Sheet Graphics
- ¥ POP Displays
- ¥ Miscellaneous

Width	Standard Heights	Base O.D.	Code
11" (280mm)	48" (1220mm)	22" x 10" x 1/8"	ARFS48-280
	60" (1524mm)	22" x 10" x 1/8"	ARFS60-280
17" (430mm)	48" (1220mm)	27-5/8" x 12 5/8" x 1/8"	ARFS48-430
	60" (1524mm)	27-5/8" x 12 5/8" x 1/8"	ARFS60-430
	66" (1676mm)	27-5/8" x 12 5/8" x 1/8"	ARFS66-430
22" (560mm)	60" (1524mm)	28-5/16" x 14-5/8" x 1/8"	ARFS60-560
	66" (1676mm)	28-5/16" x 14-5/8" x 1/8"	ARFS66-560
	72" (1829mm)	28-5/16" x 14-5/8" x 1/8"	ARFS72-560
	78" (1981mm)	28-5/16" x 14-5/8" x 1/8"	ARFS78-560
	84" (2134mm)	28-5/16" x 14-5/8" x 1/8"	ARFS84-560*

Standard Base Colors/Finishes

<u>280mm (11")</u>	<u>430mm (17") & 560mm (22")</u>
Powder Coated Steel	Powder Coated Steel
¥ Silver	¥ Silver
Painted	¥ Black
¥ 44+ Standard	Painted
¥ Custom	¥ 44+ Standard
	¥ Custom

Series 3300



Width	Heights	Code
11" (280mm)	Variable	AR3300__-280
17" (430mm)	Variable	AR3300__-430
22" (560mm)	Variable	AR3300__-560

Standard Frame Finishes

- Natural Satin Anodized
- Painted
- ¥ 44+ Standard
- ¥ Custom

Optional Divider Bar Finishes

- Natural Satin Anodized
- Polished Stainless Steel
- Painted (not recommended)

Kickplate Finishes

- Natural Satin Anodized
- Polished Stainless Steel
- Painted (not recommended)

Optional LCD Bezel Finishes

- Natural Satin Anodized
- Polished Stainless Steel

Sign Type

D-1b
Freestanding
Monitor Display

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

DateDescription


Client

University of
Nebraska at Omaha

>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

D-2
Faculty Directory

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date

Description


Client

University of
Nebraska at Omaha

>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236




Construction Details:

- APCO FullView, FV_3022(V)MF 22"(w) x 30"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert

Paper Details:

- Printed at 1200 DPI using pigment-based UV inks
- White, satin finish UV-coated photo paper with matte UV over-laminate
- Thickness of paper to be heavy enough to prevent wrinkles or waves once installed

Sign Type	
G-1 Wall Guide, Large	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	



Construction Details:

- APCO FullView, FV_2222(V)MF 22"(w) x 22"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert

Paper Details:

- Printed at 1200 DPI using pigment-based UV inks
- White, satin finish UV-coated photo paper with matte UV over-laminate
- Thickness of paper to be heavy enough to prevent wrinkles or waves once installed

Sign Type

G-2
Wall Guide, Small

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date	Description
------	-------------


Client

**University of
Nebraska at Omaha**



corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236




Construction Details:

- Acrylic window insert
- Removable printed insert


Paper Details:

- Printed at 1200 DPI using pigment-based UV inks
- White, satin finish UV-coated photo paper with matte UV over-laminate
- Thickness of paper to be heavy enough to prevent wrinkles or waves once installed


Sign Type	
G-3 Wall Guide, Acrylic	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Sign Type	
I-1 Primary Department Identifier	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	







Sign Type	
I-1a Room Monitor Display Frame	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	
57	




Sign Type	
I-2 and I-2a Room Identifier, Large	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Sign Type	
I-3 and I-3a Room Identifier, Small	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Sign Type	
I-4, I-4a, I-4b and I-4c Room Number Identifier	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	



Top view




Side view




I-5 Front view

Paper Details:

- Printed at 1200 DPI using pigment-based UV inks
- White, satin finish UV-coated photo paper with matte UV over-laminate
- Thickness of paper to be heavy enough to prevent wrinkles or waves once installed



Printed Paper Insert



Tactile and Braille Panel

Construction Details:

- APCO FullView, FV_8585(V) 8 1/2"(w) x 8 1/2"(h)
- Decorative sidebar profiles: Contour shape, Natural Satin Anodized
- Removable acrylic window and printed insert and tactile and Braille panel



I-5a Front view

- Apco Notifier Bar. Extruded aluminum channel with rollers. Adjusts automatically to grip paper or card stock up to 1/64" thick. Finish to match anodized aluminum.
- Temporary Paper insert (provided by others)

Sign Type

I-5 and I-5a
Office Identifier

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description


Client

University of
Nebraska at Omaha




corbindesign


109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



- Construction Details:**
- APCO FullView, FV_5585(V) 8 1/2"(w) x 5 1/2"(h)
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert



Sign Type	
I-6 and I-6a Office Identifier, Small	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




Top view

Side view


N-1 Front view

Construction Details:
-APCO FullView, FV_1185(V) 8 1/2"(w) x 11"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized




N-1a Front view

Construction Details:
-APCO FullView, FV_8511(V) 11"(w) x 8 1/2"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized



N-1b Front view


Construction Details:
-APCO FullView, FV_1711(V) 11"(w) x 17"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized



N-1c Front view

Construction Details:
-APCO FullView, FV_1117(V) 17"(w) x 11"(h)
-Decorative sidebar profiles: Contour shape, Natural Satin Anodized


Sign Type	
N-1, N-1a, N-1b & N-1c Notice Insert	
Scale	
1 1/2" = 1'-0" (on an 11 x 17 sheet)	
Color Code	
Notes	
This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.	
Date	Description
Client	
University of Nebraska at Omaha	
>	
corbindesign	
109 East Front Suite 304 Traverse City, MI 49684 231 947.1236	




O-1
Side View

O-1
Projecting Overhead Identifier
Front View


- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert
- Paper Details:**
- Printed at 1200 DPI using pigment-based UV inks
 - White, satin finish UV-coated photo paper with matte UV over-laminate
 - Thickness of paper to be heavy enough to prevent wrinkles or waves once installed



Printed Paper Inserts




O-2
Side View



O-2
Overhead Guide/Identifier
Front View

- Construction Details:**
- APCO FullView, large format acrylic display
 - Decorative sidebar profiles: Contour shape, Natural Satin Anodized
 - Removable acrylic window and printed insert

- Paper Details:**
- Printed at 1200 DPI using pigment-based UV inks
 - White, satin finish UV-coated photo paper with matte UV over-laminate
 - Thickness of paper to be heavy enough to prevent wrinkles or waves once installed



Alternate Single Line Layout

Sign Type

O-1 and O-2
Overhead Signs

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date


Description

Client

University of
Nebraska at Omaha

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

R-1
Regulatory

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.


Date Description

Client

University of
Nebraska at Omaha



corbindesign
109 East Front Suite 304
Traverse City, MI 49684
231 947.1236



Sign Type

T-1
Freestanding Temporary Insert

Scale

1 1/2" = 1'-0"
(on an 11 x 17 sheet)

Color Code

Notes

This drawing is design-intent only. Fabricator is responsible for fabrication and overall level of quality. Any changes in design, materials, fabrication method or other details must be approved by Corbin Design and the University of Nebraska Omaha.

Date Description

Client

University of Nebraska at Omaha

>

corbindesign

109 East Front Suite 304
Traverse City, MI 49684
231 947.1236